

COATESIA SYNTHETIC ENAMEL

Synthetic Enamel Dry Gloss Alkyd Enamel

Features

- HIGH GLOSS FINISH
- Over night DRY & RECOAT
- SINGLE PACK
- EXTENSIVE COLOUR RANGE USING COLORFAST® TINT SYSTEM
- LIMITED RANGE OF TOUCHUP SPRAYPAKS AVAILABLE

Uses

COATESIA® Synthetic TOPCOAT is ideal as a coating for steel in mild and commercial environments. The preferred coating where a over night dry, easy repair and recoat finish is required. COATESIA® Synthetic TOPCOAT is particularly suitable for use with COATESIA® Synthetic ENAMEL PRIMER for time-critical jobs.

COATESIA® Synthetic TOPCOAT is used to paint machinery and equipment such as cranes, trailers, pumps, compressors and as a general purpose dry enamel.

Specifications

Weatherability

Will chalk on exterior exposure. Chalking will not detract from the protective properties of the coating

Solvents

Compatible With Synthetic Enamel thinner

Heat Resistance

Up to 80°C dry heat

Water

Resists rain and condensation. Not recommended for permanently damp or immersed exposure

Alkalis

Not recommended where fumes, splash or spillage may occur

Abrasion

Good when fully cured

Acids

Not recommended where fumes, splash or spillage may occur

Application Conditions

For New Masonry Surfaces

- Step 1 :** Primer(1 coat) Dry-Min. 8 Hrs.
Step 2 : Putty Wall Putty Dry 6-8 Hrs.
Step 3 : Primer(1 coat) Dry. 8 Hrs.
Step 4 : Finish Synthetic Enamel(2 coats) Dry Min. 8 Hrs. in between coats.

For Metal Surfaces

- Step 1 :** Primer(1 coat) Dry-Min. 8 Hrs.
Step 2 : Putty Grey knifing Paste Filler Dry # & scuff
Step 3 : Primer(1 coat) Dry. 8 Hrs.
Step 4 : Finish Synthetic Enamel(2 coats) Dry Min. 8 Hrs. in between coats.

For Wooden Surfaces

- Step 1 :** Primer(1 coat) Dry-Min. 8 Hrs.
Step 2 : Putty Wall Putty Dry 6-8 Hrs & scuff
Step 3 : Primer(1 coat) Dry. 8 Hrs.
Step 4 : Finish Synthetic Enamel(2 coats) Dry Min. 8 Hrs. in between coats.

Surface Preparation

- Ensure the surface is clean, dry and free from all defective or poorly adhering material, dirt, grease, wax etc.
- Remove all loose or poorly adhering material by rubbing down using suitable abrasive paper and there after wipe off.
- Treat fungus affected area using Fungicidal Solution. Allow to react for 6-8 hrs.
- Apply a coat of suitable Primer followed by putty (if required) to level the dent and make surface uniform. Apply again a coat of primer
- Then apply two coat of Synthetic Enamel.

Precautions

- Don't apply when temperature falls below -10°C or rises above 60°C and when relative humidity rises above 80%. Do not apply during rain, fog or mist.
- Flammable liquid.
- Causes serious eye damage
- Causes skin irritation
- May cause an allergic skin reaction.
- Toxic to aquatic life with long lasting effects.
- Avoid release to the environment
- Collect spillage.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep out of reach of children
- Avoid breathing vapour.
- Wear protective gloves, eye or face protection
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- IF ON SKIN: Wash with plenty of water.
- Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. **Keep cool.**
- Store locked up.

Disclaimer

The data provided is as per the test carried out at the time of preparation. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee, responsibility or liability will be accepted of the results as the condition in which the products are stored, handled and used by end user is beyond our control. For consistent shade on a project / site, make sure that the batch numbers on the paint containers are the same.

Available Pack Sizes

Available in:

